

3 Feeding Options

Pile Feeder

- Electronic pile height sensor
- Solid-steel frame construction
- Holds up to 7,000 forms
- Requires only one operator
- Double front blow bar for better feeding




Shingle - Uninterrupted Feeder Continuous Load

- Maximum effeciency
- High loading capacity of 5,000 forms
- Continuous load and unload requires 2 operators
- Solid-steel frame construction
- Both forward & reverse direction for easier loading & unloading
- Front and side air blow provide complete separation & floatation
- "Easy-Set" front blow bar
- Unique leading-edge sheet sensing device

In-Line Fan-Fold Continuous or Jumbo Roll Feed

- In tandum with a roll cutter or burster
- Completely mobile the folder is equipped standard with wheels and leveling pads to allow easy transport and secure positioning to the other units.
- Also runs in-line with some Xerox and Océ imagers.





phone 888.952.4636 • 540.981.1140 infoseal.com • team@infoseal.com



Pressure Seal PS800 Folder/Sealer Quick Reference



Multiple configurations to meet any requirement.

PS800 pressure seal folder/sealer

The PS800 is undoubtedly the most cost effective, high effeciency folder/sealer available today. With a multitude of enhanced and improved features, the PS800 promises to boost your productivity - proven to run 24-7 with a processing speed of up to 40,000 8-1/2x11 forms per hour.

2 Sealing Options *12-1/2" or 18" Wide Sealing Units*

High capacity integral 8 roller system ensures a tightly sealed form.



available in the market!

Single-Wide allows for form width up to 12"

Double-Wide allows for form width up to 17-1/4"

- Doubles production, 80,000/hour
- Eliminates guillotine cutting
- Cuts laser clicks in half
- Newest technology available
- Slit on the folder at full production speed
- Specifically designed for a secure fiber tear seal across the entire 17-1/4 inches

Two-Tiered Mobile Stacker



Ergonomically designed, provides mobility, height and angle adjustment, with a 48" total collection length. Controlled speed allows for easy removal of folded & sealed pressure seal forms.

6 Foot Exit Conveyor



Technical Specification	
Processing speed	40,000 (80,000 2-wide) - 11" forms per hour - variable speed
Duty Cycle	unlimited
Form size	Max. Width 12" x Max. Depth 28" or 17-1/4" x 28" optional
Fold configurations	V, C, Z, Eccentric Z, Double Parallel and 1-Part 2-Way
Paper weights	Min. 24# - Max. 110# index card
Fold Plates	3 heavy-duty precision fabricated
Sealer	Integral 8 roller system - large diameter heavy duty
Size	Pile: 180" x 45" - Shingle: 211" x 45"
Power	208v 60Hz 3ph 30A
Warranty	Sealer: 90 days parts & labor; Folder: 90 days labor & 1 year on parts
Optional Accessories:	Code Reading Device, Center Cut, Roll in feed, Fan fold in feed, in-line with various rotary cutters

Folding Unit Features

- 3 Heavy-duty precision fabricated fold plates
- Quick paperless roller gapsets
- NEW micro-adjustment on fold plates
- Diagnostic message display
- Touch screen control panel
- Built-in batch counter with NEW variable batch • Built-in total counter
 - Shingle integrity control
 - Digital sheet gap control

• 1-1/8" diameter, removable, heavy-duty slitter shafts Sound cover included

Slitter Shafts



Quick Roller Settings







PS800 ifold Tutorial

This unique and exclusive feature is included as a standard option.

ifold offers numerous features including: • 80 job memory storage for recalling the most often used folds

• Text and pictorial tutorial screens for most applications for setup, operation, maintenance and troubleshooting

• Folder production job calculator

• Standard inch, metric and custom paper- size selection

• User-defined scheduled maintenance alerts

• 24/7 folding information availability

• And Much, Much More!